

Front View


Right Side View

Back View

Back View

1	LEDBK
2	LEDA
3	GND
4	VCC
5	RO
6	R1
7	R2
8	R3
9	R4
10	R5
11	R6
12	R7
13	G0
14	G1
15	G2
16	G3
17	G4
18	G5
19	G6
20	G7
21	B0
22	B1
23	B2
24	B3
25	B4
26	B5
27	B6
28	B7
29	GND
30	CLK
31	DISP
32	HSYNC
33	VSYNC
34	DEN
35	NC
36	GND
37	RESET
38	SDI
39	SCL
40	CS

Display Type	TFT/NOGMAU LY Beck/TRANSMISSIVE
Display Resolution	480(R) x 854
Viewing Angle	All (IPS)
LED Controller/Driver	ST7701S
Operation Temperature	-20°C ~ 70°C
Storage Temperature	-30°C ~ 80°C
Backlight Speciality	White LED Backlight
Unmounted tolerance	±0.2mm



REV	DESCRIPTION	DATE	NAME	Part No.	Customer No.	APPROVED BY	CHECKED BY	DRAWN BY	SCALE: 1:1
1		2021.11.23	h4240	R50001-480854RZ					UNIT: mm

Rondeli Electronics Co., Ltd

Materials and processes comply with "RoHS" standards