


Display Type	FT/NORMALLY Black/TRANSMISSIVE
Display Resolution	480(R,G,B)X800
Viewing Angle	ALL(IPS)
LED Controller/Driver	
Operation Temperature	-20°C ~ 70°C
Storage Temperature	-30°C ~ 80°C
Backlight Specialty	White LED Backlight
Mounting distance	±0.3mm



REV	DESCRIPTION	DATE	NAME

Part No.:		R40037-480800MZ		VER:10	
Customer No.:				PRODUCTION	
APPROVED BY:				SCALE:1:1 UNIT: mm	
CHECKED BY:				SHEET: 1 OF 1	
DRAW BY:					
DATE:		2021.11.23			
NAME:					

Rondeli Electronics Co., Ltd

Pad No.	Pad Name
1	LED+
2	LED+
3	LED+
4	NC
5	NC
6	NC
7	NC
8	LED-
9	LED-
10	LED-
11	GND
12	NC
13	GND
14	NC
15	NC
16	GND
17	DST1_D1P
18	DST1_D1N
19	GND
20	DST1_CLKP
21	DST1_CLKN
22	GND
23	DST1_D0P
24	DST1_D0N
25	GND
26	NC
27	NC
28	GND
29	LCD1D1 (NC)
30	LCD-RESSET
31	LCD1D2 (NC)
32	HOVDD
33	LCD VCC
34	LCD VCC
35	GND
36	NC
37	GND
38	NC
39	LCD1D3 (NC)
40	NC

FPC bending diagram

Solder Hot BAW
Yellow FPC BOARD

1.1MAX. please avoid